



AGS-MCCD-3U

RUGGED TRIPLE SCREEN PORTABLE DISPLAY SYSTEM



The hassle of awkwardly carrying and setting up multiple monitors at trade shows or in the field is eliminated with elegant design of the AGS-MCCD-3U. The system is light enough to be portable and rugged enough for outdoor use with sunlight readable screens.

The USB, single input upgrade enables the AGS-MCCD-3U for use with a laptop operating Windows 7 or 10.

Features:

- Triple 17.3" displays fold and stow for transport
- 52", 5760 x 1080 total resolution
- Sunlight readable
- Independent screen control
- VGA, DVI-D, and DisplayPort inputs
- Rear VESA mount

CONTACT

Acme Government Systems
1330 Mountain View Circle
Azusa, CA 91702
Sales +1.800.484.3232 Ext 2
Support +1.800.484.3232 Ext 0
Fax +1.800.484.3232
sales@acmemilspec.com
www.acmemilspec.com



AGS-MCCS-3U

Specifications:

Display	3x 17.3" displays, LED backlit 1920 x 1080 per display, 16:9
Inputs	1 x VGA, DVI-D, and DisplayPort per screen
Power	110/220 VAC, 50/60Hz
Accessories	1 power cable, 3x 6' DVI-D cables
Dimensions	H x W x D
Stowed	11.25" x 17.25" x 5.5"
Deployed @ 90°	11.25" x 47.5" x 5.5"
Deployed @ 45°	11.25" x 38" x 16"
Weight	20 lbs

Environmental

Temperature	MIL-STD-810E (501.4, 502.4)
Operating	0°C to 50°C
Non-Operating	-40°C to 70°C
Cooling	Conduction/Convection
Humidity	MIL-STD-810E (507.2)
Relative Humidity	20% to 90% operating, non-condensing 10% to 95% non-operating, non-condensing
Vibration	MIL-STD-810E (514.4)
Operating	10 to 500 Hz 1.04 G (RMS)
Non-Operating	10 to 500 Hz 1.12 G (RMS)
Shock	MIL-STD-810E (516.4)
Operating	15 G, 8 ms ½ sine
Non-Operating	40 G, 8 ms ½ sine
Drop (non-operating)	4 inches

CONTACT

Acme Government Systems
1330 Mountain View Circle
Azusa, CA 91702
Sales +1.800.484.3232 Ext 2
Support +1.800.484.3232 Ext 0
Fax +1.800.484.3232
sales@acmemilspec.com
www.acmemilspec.com