



AGS-MILPAC-III

PURPOSE BUILT C4ISR RUGGED TRIPLE SCREEN WORKSTATION

The AGS-MILPAC-III is a powerful transportable workstation, with liquid cooled dual Xeon processors and a dual RAID removable drive system.

Manufactured from high grade aluminum, with copolymer over-molded bumpers, the AGS-MILPAC-III is built to survive.



Certified for: MIL-STD-461 EMI, MIL-STD-901D lightweight class B and MIL-STD-810G temperature and humidity.

TECHNICAL SPECIFICATIONS

DISPLAY	<ul style="list-style-type: none"> 3x 17.3" FHD, 1920 x 1080
KEYBOARD	<ul style="list-style-type: none"> Removable keyboard touchpad module with integrated CAC reader
PERFORMANCE	<ul style="list-style-type: none"> 2x Liquid Cooled Xeon CPUs Upto 512GB ECC RAM 2x Removable 2TB SSD 3x Removable 8TB HDD
FEATURES	<ul style="list-style-type: none"> 3x HDMI cloning ports (1 per display) Multicard reader Slot load bluray eSATAp, RS232, and NIC
DIMENSIONS	<ul style="list-style-type: none"> Stowed: 14.625" x 17.25" x 12" Deployed @ 90° 15.25" x 48.0" x 11.75" Deployed @ 45° 15.25" x 43.0" x 18.75"
WEIGHT	<ul style="list-style-type: none"> 65lbs

ENVIRONMENTAL

TEMPERATURE	<ul style="list-style-type: none"> MIL-STD-810G (514.5) Op 0°C to 50°C Non-Op -25°C to 70°C
HUMIDITY	<ul style="list-style-type: none"> MIL-STD-810G (507.2) 20% to 80% op/non-op, non-condensing
VIBRATION	<ul style="list-style-type: none"> MIL-STD-810G (514.4) Op 10 to 500 Hz 0.4 G (RMS) Non-Op 10 to 500 Hz 1.12 G (RMS)
SHOCK	<ul style="list-style-type: none"> MIL-STD-810G (516.4) Op 15 G, 8 ms ½ sine Non-Op 40 G, 8 ms ½ sine
HIGH IMPACT SHOCK	<ul style="list-style-type: none"> MIL-STD-901D Lightweight shock, Class B